



RAVENNA: 12V Solid Brass Up Light

CL-BL23-III Weathered Solid Brass Bullet Light

NOTEABLE FEATURES:

- ❑ WEIGHT: 3.2 lbs
- ❑ ADJUSTABLE SHROUD TO PREVENT LIGHT GLARE
- ❑ BERYLLIUM COPPER SOCKET WITH SS MR-16 CLIP
- ❑ PRE-GREASED SOCKET AND MACHINED THREADS
- ❑ FLUSH GLASS LENS TO PREVENT DEBRIS BUILD-UP
- ❑ MANUFACTURED FROM C260 & C360 SOLID BRASS
- ❑ LIFETIME WARRANTY
- ❑ SLOTTED STAKE FOR EASY SERVICING
- ❑ TRIPLE LEAD THREAD SCREW ON TOP
- ❑ MANUFACTURED IN GREENSBORO, NC, USA

OPTIONAL ACCESSORIES:

- ❑ WEATHERED BRASS SURFACE MOUNT (CL-TM23-III)
- ❑ WEATHERED BRASS RISERS (BLEP-III: 6", 12", 24", 36")
- ❑ WEATHERED BRASS COUPLER (CL-COUP-III)
- ❑ WEATHERED BRASS 90 DEGREE FITTING (CL-90DE-III)
- ❑ OPTIONAL LENSES & LOUVERS (See website for details)
- ❑ WIDE RANGE OF MR-16 LAMPS & LEDs



PATENTED DESIGN



SPECIFICATIONS:

Our Commitment

At ClaroLux®, our goal is to set the standard in the landscape lighting industry. We are happy to be the exception, not the rule. Every day we challenge ourselves to create new and innovative products that can help revolutionize the low voltage lighting industry. We pride ourselves on being innovative, passionate, and dedicated to setting the standard. What you will find when you purchase from ClaroLux Landscape Lighting® is that the norm is never good enough. We believe in our mission, we believe in ourselves, and we believe in our products. This is why our products come with a structural lifetime warranty.

Body

Machined brass bar stock and brass pipe. Body design provides enclosed, water resistant wireway to protect wires. The top and base come with a triple lead thread pattern which creates easy opening and closing of the fixture. Fixture weight is 3.2 lbs.

Gasket

High temperature silicone o-ring for water-tight seal.

Knuckle

Machined brass knuckle with a solid brass adjustable thumbscrew. Vertical tilt of -30° to +210° for precise final adjustment. Thread on the knuckle is 1/2 NPS which easily threads into ClaroLux's® patented ground stake and fixture accessories.

Shroud

Precision machined US brass pipe and comes with a factory sealed shock resistant tempered glass lens to prevent water intrusion. Accepts up to one additional lens/hex cell accessory. Shroud is adjustable to prevent glare and rotatable 360°.

Lens

Comes with a factory sealed shock resistant tempered borosilicate glass lens to prevent water intrusion. Glass lens sits flush with top to prevent debris/water buildup. A complete set of optical designer lenses including: spread lens, frosted, hex cell also available.

Lamp

For use with a halogen lamp up to 35W MR16 lamp. Brilliance LED MR16 lamps are available in 4W, 5W or 7W.

Electrical Requirements

A remote 12V transformer required, may be ordered separately from ClaroLux®. Recommended voltage range for 12V halogen lamps is 10.8V - 12V. Recommended voltage range for 12V Brilliance LEDs is 10V - 14V (12V is ideal).

Lamp Connection

Spring loaded, pre-greased beryllium copper socket with stainless steel MR16 lamp holder. GU5.3 base.

Mounting Stake

Standard mounting stake is injection molded ABS with a 1/2" NPS threaded female fitting. Comes with wire slot so luminaire can easily be removed and serviced. The stake color is dark brown to help blend in with the landscape environment.

Wiring

25ft of 16AWG UL Listed, copper wire that is protected by Black Polyvinyl Chloride (PVC). ClaroLux® recommends using copper crimp, lithium filled, grease tube connectors at each connection point in the field (HUB).

Finish

ClaroLux's® Weathered Brass finish was created especially for ClaroLux's brass luminaire line. ClaroLux's brass luminaires are all stained and manufactured in the USA. The Ravenna has a "living finish" and will naturally patina and change over time.

Warranty

ClaroLux's® Structural Lifetime Warranty (please see warranty for more details).

Manufacturing

Proudly made at ClaroLux's® manufacturing facility in Greensboro, NC, USA.