



**PALLANZA:** 12V Nickel Plated Grill Light

**CL-GL1 Nickel Plated Grill Light**

**NOTEABLE FEATURES:**

- ❑ WEIGHT: 3.3 lbs
- ❑ ROTATABLE SHROUD TO PREVENT LIGHT GLARE
- ❑ BERYLLIUM COPPER SOCKET WITH SS MR-16 CLIP
- ❑ PRE-GREASED SOCKET AND MACHINED THREADS
- ❑ FLUSH MOUNTED CLEAR GLASS LENS
- ❑ NICKEL PLATED
- ❑ LIFETIME WARRANTY
- ❑ ADJUSTABLE ARM
- ❑ DESIGNED IN GREENSBORO, NC, USA

**OPTIONAL ACCESSORIES:**

- ❑ OPTIONAL PLASTIC R-CLAMPS FOR ATTACHING THE WIRE
- ❑ OPTIONAL LENSES & LOUVERS (See website for details)
- ❑ WIDE RANGE OF MR-16 LAMPS & LEDs



**SPECIFICATIONS:**

**Our Commitment**

At ClaroLux®, our goal is to set the standard in the landscape lighting industry. We are happy to be the exception, not the rule. Every day we challenge ourselves to create new and innovative products that can help revolutionize the low voltage lighting industry. We pride ourselves on being innovative, passionate, and dedicated to setting the standard. What you will find when you purchase from ClaroLux Landscape Lighting® is that the norm is never good enough. We believe in our mission, we believe in ourselves, and we believe in our products. This is why our products come with a structural lifetime warranty.

**Body**

Machined cast aluminum casting with nickel plated coating. Body design provides enclosed, water resistant wireway to protect wires. The top and base come with a single lead thread mini thumbscrew which creates easy opening and closing of the fixture. Fixture weight is 3.3 lbs.

**Gasket**

High temperature silicone o-ring for water-tight seal.

**Adjustable Arm**

The adjustable arm on the Pallanza allows for easy and precise adjustment of the luminaire. Adjustable arm allows the luminaire to be aimed in any direction.

**Shroud**

Precision machined nickel plated aluminum shroud. Accepts up to one additional lens/hex cell accessory. The extended shroud is rotatable 360° to prevent glare.

**Lens**

Comes with a factory sealed shock resistant tempered borosilicate glass lens to prevent water intrusion. The clear glass lens sits flush with top of the luminaire. A complete set of optical designer lenses including: spread lens, frosted, hex cell also available.

**Lamp**

For use with a halogen lamp up to 35W MR16 lamp. Brilliance LED MR16 lamps are available in 4W, 5W or 7W.

**Electrical Requirements**

A remote 12V transformer required, may be ordered separately from ClaroLux®. Recommended voltage range for 12V halogen lamps is 10.8V - 12V. Recommended voltage range for Brilliance 12V LEDs is 10V - 14V (12V is ideal).

**Lamp Connection**

Spring loaded, pre-greased beryllium copper socket with stainless steel MR16 lamp holder. GU5.3 base.

**Surface Mount**

Surface mount is nickel plated cast aluminum. Comes with push button switch so luminaire can easily be turned on/off.

**Wiring**

25ft of 18AWG UL Listed, copper wire that is protected by Black Polyvinyl Chloride (PVC). ClaroLux® recommends using copper crimp, lithium filled, grease tube connectors at each connection point in the field (HUB).

**Finish**

ClaroLux's® Nickel Plated finish gives the luminaire a beautiful uniform look. Overtime the Pallanza luminaire will not patina. ClaroLux's® grill light luminaires are designed in the USA.

**Warranty**

ClaroLux's® Structural Lifetime Warranty (please see warranty for more details).

**Manufacturing**

Proudly designed at ClaroLux's® manufacturing facility in Greensboro, NC, USA.