



CLAYTON: 12V Solid Brass Area Light

CL-AL26-III Weathered Solid Brass Area Light

NOTEABLE FEATURES:

- ❑ OPTIONAL RISER POLES AVAILABLE
- ❑ 3M POWDER COATED INTERIOR
- ❑ BERYLLIUM COPPER SOCKET
- ❑ PRE-GREASED SOCKET AND MACHINED THREADS
- ❑ CLEAR BOROSILICATE GLASS LENS
- ❑ MANUFACTURED FROM C260 & C360 SOLID BRASS
- ❑ LIFETIME WARRANTY
- ❑ SLOTTED STAKE FOR EASY SERVICING
- ❑ CNC MACHINED SHROUD/COLLAR/STEM
- ❑ MANUFACTURED IN GREENSBORO, NC, USA

OPTIONAL ACCESSORIES:

- ❑ WEATHERED BRASS SURFACE MOUNT (CL-TM23-III)
- ❑ WEATHERED BRASS RISERS (Check Website for details)
- ❑ WIDE RANGE OF BI-PIN LAMPS & LEDs



CLAROLUX® landscape lighting fixtures are available with LED lamps.

PATENTED DESIGN



SPECIFICATIONS:

Our Commitment

At ClaroLux®, our goal is to set the standard in the landscape lighting industry. We are happy to be the exception, not the rule. Every day we challenge ourselves to create new and innovative products that can help revolutionize the low voltage lighting industry. We pride ourselves on being innovative, passionate, and dedicated to setting the standard. What you will find when you purchase from ClaroLux Landscape Lighting® is that the norm is never good enough. We believe in our mission, we believe in ourselves, and we believe in our products. This is why our products come with a structural lifetime warranty.

Body

Machined from US grade solid brass bar stock. Body design provides enclosed, water resistant wireway to protect wires. Features an integral knuckle for maximum mechanical strength.

Gasket

High temperature silicone o-rings for water-tight seal.

Knuckle

Machined brass knuckle with a solid brass adjustable thumbscrew. Vertical tilt of -30° to +210° for precise final adjustment. Thread on the knuckle is 1/2 NPS which easily threads into ClaroLux's® patented ground stake and fixture accessories.

Shroud

Precision machined US grade brass bar stock that comes with a factory sealed shock resistant tempered glass lens to prevent water intrusion. The shroud is locked into place with one stainless steel mini-set screw.

Lens

Comes with a factory sealed shock resistant tempered borosilicate glass lens to prevent water intrusion. Glass lens is clear (Optional frosted lens is available).

Lamp

For use with a halogen lamp up to 20W T3 bi-pin lamp. Brilliance LED bi-pin lamps are available (see website for details).

Electrical Requirements

A remote 12V transformer required, may be ordered separately from ClaroLux®. Recommended voltage range for 12V halogen lamps is 10.8V - 12V. Recommended voltage range for 12V Brilliance LEDs is 10V - 14V (12V is ideal).

Lamp Connection

Spring loaded, pre-greased beryllium copper socket. GU5.3 base.

Mounting Stake

Standard mounting stake is injection molded ABS with a 1/2" NPS threaded female fitting. Comes with wire slot so luminaire can easily be removed and serviced. The stake color is dark brown to help blend in with the landscape environment.

Wiring

25ft of 18AWG UL Listed, copper wire that is protected by Black Polyvinyl Chloride (PVC). ClaroLux® recommends using copper crimp, lithium filled, grease tube connectors at each connection point in the field (HUB).

Finish

ClaroLux's® Weathered Brass finish was created especially for ClaroLux's brass luminaire line. The Clayton has a "living finish" and will naturally patina and change over time.

Warranty

ClaroLux's® Structural Lifetime Warranty (please see warranty for more details).

Manufacturing

Proudly made at ClaroLux's® manufacturing facility in Greensboro, NC, USA.