



FASANO-D: 12V Solid Brass Specialty Wash/Deck Light

CL-SWL1-III-D



CLAROLUX[®] landscape lighting fixtures are available with LED lamps.



PATENTED DESIGN

NOTEABLE FEATURES:

- ❑ WEIGHT: 2.4 lbs
- ❑ EXTENDED SHROUD TO PREVENT LIGHT GLARE
- ❑ PRE-GREASED, BERYLLIUM COPPER SOCKET
- ❑ PRE-DRILLED HOLES FOR EASY SURFACE MOUNTING
- ❑ FROSTED BOROSILICATE GLASS LENS
- ❑ SOLID CAST BRASS CONSTRUCTION
- ❑ LIFETIME WARRANTY

NOTEABLE FEATURES CONTINUED:

- ❑ 1/2"-NPS THREADED NIPPLE FOR CONDUIT
- ❑ PATENTED DESIGN
- ❑ STAINLESS STEEL SCREWS FOR TOP
- ❑ ASSEMBLED IN GREENSBORO, NC, USA

OPTIONAL ACCESSORIES:

- ❑ DADOED WOOD SLATS (If surface mounting to deck/dock)
- ❑ WIDE RANGE OF BI-PIN LAMPS & LEDs

SPECIFICATIONS:

Our Commitment

At ClaroLux[®], our goal is to set the standard in the landscape lighting industry. We are happy to be the exception, not the rule. Every day we challenge ourselves to create new and innovative products that can help revolutionize the low voltage lighting industry. We pride ourselves on being innovative, passionate, and dedicated to setting the standard. What you will find when you purchase from ClaroLux Landscape Lighting[®] is that the norm is never good enough. We believe in our mission, we believe in ourselves, and we believe in our products. This is why our products come with a structural lifetime warranty.

Body

Solid cast brass body. Body design provides enclosed, water resistant wireway to protect wires. The top and base come with three stainless steel screws which creates easy opening and closing of the fixture. Fixture weight is 2.4 lbs.

Gasket

High temperature silicone o-ring for water-tight seal.

Shroud

Cast brass patented body design that comes with a factory sealed, frosted, shock resistant, tempered glass lens to prevent water intrusion. The extended shroud was perfectly designed to prevent light glare.

Lens

Comes with a factory sealed shock resistant tempered borosilicate, frosted glass lens to prevent water intrusion. The frosted glass lens is inset with the front of the luminaire to prevent light glare.

Lamp

For use with a halogen lamp up to 20W T3 Bi-Pin lamp. A wide range of LED lamps are available for the Fasano.

Electrical Requirements

A remote 12V transformer required, may be ordered separately from ClaroLux[®]. Recommended voltage range for 12V halogen lamps is 10.8V - 12V. Recommended voltage range for 12V LEDs is 10V - 14V.

Lamp Connection

Spring loaded, pre-greased beryllium copper socket. GU5.3 base.

Built-In Surface Mount

The base of the luminaire acts as a built-in surface mount which is cast brass. Comes with pre-cast mounting knockout holes so luminaire can easily be surface mounted.

Wiring

25ft of 16AWG UL Listed, copper wire that is protected by Black Polyvinyl Chloride (PVC). ClaroLux[®] recommends using copper crimp, lithium filled, grease tube connectors at each connection point in the field (HUB).

Finish

ClaroLux's[®] Weathered Brass finish was created especially for ClaroLux's brass luminaire line. ClaroLux's[®] Fasano brass luminaires are all stained and assembled in the USA. The Fasano has a "living finish" and will naturally patina and change over time.

Warranty

ClaroLux's[®] Structural Lifetime Warranty (please see warranty for more details).

Manufacturing

Proudly stained and assembled at ClaroLux's[®] manufacturing facility in Greensboro, NC, USA.